### CHARGERS FOR STARTER BATTERIES

## AQ-TRON®

#### INTELLIGENT BATTERY CHARGER

**BATTERY** SUPPLIES®

Switching Power Charger includes most advanced charging technology and lead this charger into next level.

#### **BAT/44459**

#### **FEATURES**

- CE version: 220V 240V
- Automatic charge condition monitoring
- 8 bit LED status indicator & dip switch panel
- Reversed polarity prevention & Battery condition detect •
- Battery plate desulfates / re-conditions assist technology •
- Over temperature / Over current / Reverse connect protection

#### **NEW FUNCTIONS**

AO-TRON Intelligent Battery Charge

- Memory
- Car charger Lithium + LiFePO4 batterv

Input power (V)	Charge Rate (A)	Battery type	Product Dim.	Weight (CTN)
6/12/24V	6-12V-20A, 10A, 2A 24V-10A, 5A, 2A	Reg/AGM/ (12V)Deep cycle/(6/12V)GEL	24.6 x 14.6 x 12.1 cm	NW: 9.6 kgs

#### **SMART BATTERY CHARGERS**

Use our energy source if you have start difficulties due to insufficient battery capacity in the vehicle battery or use it as charger for 12V/24V lead-acid (starter)batteries. Due to its wheels and hand-grips the battery chargers are very easy transportable.

The battery charger Boosters are professional battery chargers for charging and fast-charging the 12V & 24V lead-acid batteries.

	Model	BAT/45680	Innun man	
	Input Voltage (V)	230		
	Charge Voltage (V)	12/24		
	Effective Charging Current (A)	10A		
T	Effective Charging Boost (A)	14A	AQ-TR	ON
	Class of Insulation	Н		2
	Rated charging Current (A)	8.0/5.0		
	Max rated reference capacity (Ah)	120		
	Min rated reference capacity (Ah)	25	SUN S	
	Weight (kg)	7.2		
	External Dimension (cm)	26x23x19.7	- <u>48</u> 1	
	External Dimension (cm)	26x23x19.7		
	External Dimension (cm) Model	26x23x19.7 BAT/45684	BAT/45685	BAT/45686
			BAT/45685 230	<b>BAT/45686</b> 230
	Model	BAT/45684		
on	Model Input Model (V)	<b>BAT/45684</b> 230	230	230
TROAS	Model Input Model (V) Max Charging current (A)	BAT/45684 230 150 12/24	230 200	230 250
BATTERY CHARGE	Model Input Model (V) Max Charging current (A) Charging Voltage (V) Charge Current	BAT/45684 230 150 12/24	230 200 12/24	230 250 12/24
	Model Input Model (V) Max Charging current (A) Charging Voltage (V) Charge Current Max reference capacity (Ah)	BAT/45684 230 150 12/24 5A/10A/20A/30A	230 200 12/24 5A/15A/30/40A 450Ah	230 250 12/24 10A/20A/35A/50A 550Ah
	Model Input Model (V) Max Charging current (A) Charging Voltage (V) Charge Current Max reference capacity (Ah)	BAT/45684 230 150 12/24 5A/10A/20A/30A 400Ah	230 200 12/24 5A/15A/30/40A 450Ah	230 250 12/24 10A/20A/35A/50A 550Ah

# 6-12-24 VOLT FOR OPEN LEAD - AGM - GEL & DEEP CYCLE

**BATTERY SUPPLIES.BE** 43