

Chargers

EV CHARGING STATIONS



CHARGING STATION TO CHARGE AT YOUR HOME OR COMPANY

A charging station can be easily installed at your home. All you have to do is plug in the cable and you can start charging at a higher speed than with a Portable charger. An EV charging station guarantees faster charging of your electric car.

You can choose between different capacities of charging stations 7, 11 & 22KW and you have the choice between different charging plugs type 1 & 2.

The EV charging stations are equipped with a socket. This allows you to charge different types of electric vehicles with 1 car charging station. This requires a compatible charging cable.



- IP67 and wall mount / stand installation provides high adaptability
- CE UL TUV certificate



Standard provided for wall mounting.

◀ **BAT/49503 - Mounting post**

Optional

◀ **BAT/49660 - Plug holder**

for plug type 1

◀ **BAT/49661 - Plug holder**

for plug type 2

Reference	BAT/49491	BAT/49492	BAT/49493
Input Voltage (V)	230 ± 20%	400 ± 20%	400 ± 20%
Phase	1 phase	3 phase	3 phase
Output Voltage (V)	230 ± 20%	400 ± 20%	400 ± 20%
Output Current (A)	32	16	32
Total Power (kW)	7,4	11	22
Charging Interface	Type2	Type2	Type2
Operating Temperature	-30 °C to +60 °C	-30 °C to +60 °C	-30 °C to +60 °C
Storage Temperature	-40 °C to +80 °C	-40 °C to +80 °C	-40 °C to +80 °C
Protection Class	IP65	IP65	IP65
Weight (kg)	3,51	3,7	3,85
Dimension (W x H x D) (mm)	320 x 200 x 95	320 x 200 x 95	320 x 200 x 95

PORTABLE CHARGER

With a portable charger you can easily and safely charge your electric car from a standard household power outlet.



Reference	BAT/49494	BAT/49495
Install	plug TYPE 1	plug TYPE 2
Rated Voltage (V)	250	250
Rated Frequency (Hz)	50 / 60	50 / 60
Adjustable Current	6A min.- 16A max	6A min.- 16A max
Rated Power (kW)	3,8	3,8
Charging Cable Length	5m	5m
Operating Temperature	-30 °C to +65 °C	-30 °C to +65 °C
Storage Temperature	-40 °C to +80 °C	-40 °C to +80 °C
Protection Class	IP65	IP65
Control Box Size (mm)	255 x 109 x 55	255 x 109 x 55
Weight (kg)	3,4	3,4

CHARGING CABLE

A charging cable is an important part to safely charge your electric car. With a quality charging cable you can charge safely both at home and in public. As soon as the charging point is equipped with a Mennekes socket, you can charge with any charging cable.

A charging cable always consists of a rubber charging cable with a charging plug and a type 1 or type 2 charging plug depending on your type of vehicle.



Type 1



Type 2



Reference	BAT/49496	BAT/49497	BAT/49498	BAT/49499	BAT/49500	BAT/49501
Type plug	Type 1 - Type 2	Type 1 - Type 2	Type2 - Type 2	Type2 - Type 2	Type2 - Type 2	Type2 - Type 2
Rated Voltage (V)	AC 250	AC 250	AC 250	AC 480	AC 250	AC 480
Rated Current (A)	16 / Single Phase	32 / Single Phase	16 / Single Phase	16 / Three phase	32 / Single Phase	32 / Three phase
Charging Cable Length (m)	5	5	5	5	5	5
Operating Temperature	-30 °C to +65 °C	-30 °C to +65 °C	-30 °C to +65 °C	-30 °C to +65 °C	-30 °C to +65 °C	-30 °C to +65 °C
Storage Temperature	-40 °C to +70 °C	-40 °C to +70 °C	-40 °C to +70 °C	-40 °C to +70 °C	-40 °C to +70 °C	-40 °C to +70 °C
Protection Class	IP55	IP55	IP55	IP55	IP55	IP55

REPAIR

If you have a faulty charger or part, our electronics department can repair it and even provide you with a replacement during the period your part is being repaired.

Do you have old parts lying around? If they're repairable, we are interested in buying them! More info at page 150.

