



BATTERY BOOSTERS

STANDARD BOOSTERS

AQ-TRON®

BAT/44891

FEATURES

- 12V Portable Booster Pack
- Battery 12V - 17Ah*1
- Peak Amp: 1700 Amp ; 500 CCA
- 12V Automatic 4 stage switching charger 12V-2A
- Maximum Charging Voltage - 14.7VDC
- Built-in Anti-Surge Protector
- Reverse connection buzzer when output at OFF
- Military grade, unbreakable one-piece Housing (HDPE - High Density Polyethylene)
- Industrial illuminant voltmeter
- DC Cable: #4 Gauge/22mm², length 152 cm
- Clamp: Plastic insulation, 30% nylon w/rugged
- Alligator clamp fixture
- Dimensions: 36 x 23 x 41 cm
- Weight: 10 kg



BAT/44892

FEATURES

- 12V-24V Portable Booster Pack
- Battery 12V - 17Ah*2
- 12V 3400 Amp ; 1000 CCA
- 24V 1700 Amp ; 500 CCA
- 12V Automatic 4 stage switching charger 12V-2A
- Maximum Charging Voltage - 14.7VDC
- Built-in Anti-Surge Protector
- Reverse connection buzzer when output at OFF
- Military grade, unbreakable one-piece Housing (HDPE - High Density Polyethylene)
- Industrial illuminant voltmeter
- DC Cable: #4 Gauge/22mm², length 152 cm
- Clamp: Plastic insulation, 30% nylon w/rugged
- Alligator clamp fixture
- Dimensions: 36 x 23 x 41 cm
- Weight: 17,5 kg



NO-TRON

LI-ION BOOSTER
12V/24 LITHIUM BOOSTER PACK

BAT/45869



**IN-&
OUTDOOR
SERIES**

**CAR JUMP
START+SURGE
PROTECTOR**

FEATURES

- 12V True Li-Ion battery
- Built in 12-24V Surge Protector
- Reverse connection buzzer & LED when output at OFF position
- Military grade , unbreakable one-piece housing
- HDPE - High Density Polyethylene
- DC Cable 2AWG, length-5ft Rubber insulation, copper jaws
- Industrial illuminant voltmeter

SPECIFICATIONS

Model No.	BAT/45869
Dimension	36 x 21 x 41 cm
Capacity	High Efficiency true LiFePO4 battery *2
Gross Weight	9 kg
Net Weight	8 kg
Input	C0210022 12V/2A Fast charger
Peak Current	12V-4600 Peak AMPS 24V-2300 Peak AMPS
Product Certificate	CE / FCC
Factory Certificate	ISO9001 / 14001

FUSES FOR STANDARD CHARGERS

Ref.	Amp.	Centre distance
BAT/48596	300 A	40 mm
BAT/48597	500 A	40 mm
BAT/38188	500 A	50 mm
BAT/48598	1000 A	40 mm